

# Wall2Floor Top Coat Fine

Mineral coating for internal and external horizontal and vertical surfaces.

**PRODUCT DESCRIPTION** Wall2Floor Top Coat Fine is a mineral coating, for the decoration of internal and external horizontal and vertical surfaces.

## APPLICATIONS

Interior decoration of high quality, in line with the most modern and current trends in "concrete" in the field of architecture.

## IDENTIFICATION CHARACTERISTICS

Paste product.

## PERFORMANCE CHARACTERISTICS

Thanks to its particular formulation, it allows to obtain a continuous and seamless surface.

## SUPPORT PREPARATION

Consult the technical data sheet of "Wall2Floor system".

## APPLICATION

Consult the technical data sheet of "Wall2Floor system".

## MIXTURE PREPARATION

Add to each 15 kg pack Wall2Floor Top Coat Fine, before installation, a 5 kg pack of

Wall2Floor Component B, with the aid of a mechanical mixer equipped with a whisk.

Mix the mixture for about three minutes, the mixture obtained must not have lumps, unmixed portions of the components, impurities.

**Dilution** : when the two components are completely mixed, it is possible to add up to 5% of water.

**Life time of the dough** : about 90 minutes.

## RECOMMENDATIONS

During all phases of preparation of the substrate, products and application, the correct use of equipment and personal protective equipment (dpi) is recommended.

Do not expose the products for long periods to direct heat sources or temperatures below + 5 ° C.

If the products are stored at temperatures close to + 5 ° C, we recommend that you take them to a suitable temperature before use, in order to condition them at a temperature of use not lower than + 10 ° C. Do not heat the products using a direct source of heat, flame, hot body or similar. We recommend that you finish each job with materials from the same manufacturing batch. If different manufactures are used, it is advisable to mix the various productions together in order to avoid slight differences in shades. The external application of the "Wall2Floor system" involves choosing light colors and using exterior resistant dyes. After application, the surfaces must be protected from rain and humidity, until completely dry.

Exposure to the atmospheric agents of the not completely dry surface can generate the appearance of irreversible stains or bleaching phenomena.

For the correct use of the mentioned materials, dilution and installation, please refer to a careful reading of the relative technical data sheet.

During all phases of preparation of the substrate, products and application, the correct use of equipment and personal protective equipment (dpi) is recommended.

## CLEANING OF TOOLS

With water immediately after use.

**YIELD** Wall2Floor Top Coat Fine: 1.0-1.2 kg / m<sup>2</sup>, in the two layers, based on the type of intervention and the state of the support. It is advisable to check the actual yield with a preliminary test on the specific support.

**COLORS** White and color chart Wall2Floor.

## PACKING

Packs of 15 kg.

## STORAGE TERMS

The material has a duration in the original and well sealed container of about 24 months as long as it is stored in a covered warehouse at a temperature between + 10 ° C and + 30 ° C.

## SAFETY INDICATIONS

Directive 2004/42 / CE:

Wall2Floor Top Coat Fine (paints for decorative effects): EU limit value for Wall2Floor Top Coat Fine (cat A / I): 200 g / l (2010)

Wall2Floor Top Coat Fine contains a maximum of 200 g / l of VOC

The product does not require labeling in accordance with the regulations in force.

Use the product according to current hygiene and safety standards. Do not throw residues into sewers, waterways and on the ground; after use do not disperse the containers in the environment, allow the residues to dry well and treat them as special waste. Keep out of reach of children. If swallowed, seek medical advice immediately. For further information consult the safety data sheet.

NB- COLORIFICIO NOVACOLOR guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge; however, it cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for each specific case. This cancels and replaces any previous card.