

## Safety Data Sheet

### ECLAT\_WALL PAINTING

Safety Data Sheet dated 10/5/2017, version 2

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier  
Mixture identification:  
Trade name: ECLAT\_WALL PAINTING  
Trade code: N363
- 1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use:  
Coating material
- 1.3. Details of the supplier of the safety data sheet  
Company:  
NOVACOLOR S.R.L  
Via U. Aldrovandi, 10  
47122 Forlì (FC) - Italy -  
Tel. +39 0543 401840  
Fax. +39 0543 414585  
Competent person responsible for the safety data sheet:  
reach@novacolor.biz
- 1.4. Emergency telephone number  
Technical information: NOVACOLOR SRL +39 0543 401840 (Monday – Friday 8.00-12.00 ;  
13.30-17.30)

---

#### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture  
EC regulation criteria 1272/2008 (CLP)  
Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.  
Adverse physicochemical, human health and environmental effects:  
No other hazards
- 2.2. Label elements  
Hazard pictograms:  
None  
Hazard statements:  
H412 Harmful to aquatic life with long lasting effects.  
Precautionary statements:  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P273 Avoid release to the environment.  
P501 Dispose of contents in accordance with national regulation.  
Special Provisions:  
EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.  
EUH208 Contains reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]  
and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.  
Special provisions according to Annex XVII of REACH and subsequent amendments:  
None
- 2.3. Other hazards  
vPvB Substances: None - PBT Substances: None  
Other Hazards:  
No other hazards

---

#### SECTION 3: Composition/information on ingredients

N363/2

Page n. 1 of 10

## Safety Data Sheet

### ECLAT\_WALL PAINTING

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 1% - < 3%	2-(2-butoxyethoxy) ethanol	Index number: 603-096-00-8 CAS: 112-34-5 EC: 203-961-6 REACH No.: 01-2119475104-44-XXXX	⚠ 3.3/2 Eye Irrit. 2 H319
>= 0.1% - < 0.25%	ethylene glycol	Index number: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH No.: 01-2119456816-28-xxxx	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.9/2 STOT RE 2 H373
>= 0.005% - < 0.05%	1,2-benzisothiazol- 3(2H)-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	⚠ 3.1/2/Inhal Acute Tox. 2 H330 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=1. ⚠ 4.1/C2 Aquatic Chronic 2 H411 M=1.
>= 0.005% - < 0.05%	terbutryn	CAS: 886-50-0 EC: 212-950-5	⚠ 4.1/A1 Aquatic Acute 1 H400 M=100. ⚠ 4.1/C1 Aquatic Chronic 1 H410 M=100. ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.4.2/1B Skin Sens. 1B H317
>= 0.0015% - < 0.0015%	reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: 613-167-00-5 CAS: 55965-84-9 EC: 611-341-5	⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.4.2/1A Skin Sens. 1A H317 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=100. ⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10. ⚠ 3.1/3/Oral Acute Tox. 3 H301 ⚠ 3.1/3/Dermal Acute Tox. 3 H311 ⚠ 3.1/1/Inhal Acute Tox. 1 H330

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

## Safety Data Sheet

### ECLAT\_WALL PAINTING

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

---

#### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

## Safety Data Sheet

### ECLAT\_WALL PAINTING

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

---

#### SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

- OEL Type: EU - TWA(8h): 67.5 mg/m<sup>3</sup>, 10 ppm - STEL: 101.2 mg/m<sup>3</sup>, 15 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

- OEL Type: ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

ethylene glycol - CAS: 107-21-1

- OEL Type: EU - TWA(8h): 52 mg/m<sup>3</sup>, 20 ppm - STEL: 104 mg/m<sup>3</sup>, 40 ppm - Notes:

Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

- OEL Type: ACGIH - STEL: Ceiling 100 mg/m<sup>3</sup> - Notes: A4 (H) - URT and eye irr

DNEL Exposure Limit Values

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

Worker Professional: 1.25 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 50.6 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 67.5 mg/m<sup>3</sup> - Consumer: 34 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 67.5 mg/m<sup>3</sup> - Consumer: 34 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 20 mg/kg - Consumer: 10 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

ethylene glycol - CAS: 107-21-1

Worker Professional: 35 mg/m<sup>3</sup> - Consumer: 7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 106 mg/kg - Consumer: 53 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

Target: Fresh Water - Value: 1 mg/l

Target: Marine water - Value: 0.1 mg/l

Target: Freshwater sediments - Value: 4 mg/kg

Target: Marine water sediments - Value: 0.4 mg/kg

Target: Microorganisms in sewage treatments - Value: 200 mg/l

Target: Food chain - Value: 56 mg/kg

Target: Soil (agricultural) - Value: 0.4 mg/kg

ethylene glycol - CAS: 107-21-1

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: Freshwater sediments - Value: 37 mg/kg

Target: Marine water sediments - Value: 3.7 mg/kg

Target: Microorganisms in sewage treatments - Value: 199.5 mg/l

Target: Soil (agricultural) - Value: 1.53 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

## Safety Data Sheet

### ECLAT\_WALL PAINTING

Protection for hands:  
Not needed for normal use.  
Respiratory protection:  
Not needed for normal use.  
Thermal Hazards:  
None  
Environmental exposure controls:  
None  
Appropriate engineering controls:  
None

---

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

Appearance:	liquid	
Colour:	various	
Odour:	characteristic	
Odour threshold:	N.A.	
pH:	9	
Melting point / freezing point:	N.A.	
Initial boiling point and boiling range:	N.A.	
Solid/gas flammability:	N.A.	
Upper/lower flammability or explosive limits:		N.A.
Vapour density:	N.A.	
Flash point:	N.A.	
Evaporation rate:	N.A.	
Vapour pressure:	N.A.	
Relative density:	1.09 kg/l	
Solubility in oil:	N.A.	
Partition coefficient (n-octanol/water):	N.A.	
Auto-ignition temperature:	N.A.	
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	

##### 9.2. Other information

Miscibility:	N.A.	
Fat Solubility:	N.A.	
Conductivity:	N.A.	
Substance Groups relevant properties		N.A.

---

#### SECTION 10: Stability and reactivity

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
None
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

---

#### SECTION 11: Toxicological information

- 11.1. Information on toxicological effects

## Safety Data Sheet

### ECLAT\_WALL PAINTING

Toxicological information of the product:

ECLAT\_WALL PAINTING

- a) acute toxicity  
Not classified  
No data available for the product
- b) skin corrosion/irritation  
Not classified  
No data available for the product
- c) serious eye damage/irritation  
Not classified  
No data available for the product
- d) respiratory or skin sensitisation  
Not classified  
No data available for the product
- e) germ cell mutagenicity  
Not classified  
No data available for the product
- f) carcinogenicity  
Not classified  
No data available for the product
- g) reproductive toxicity  
Not classified  
No data available for the product
- h) STOT-single exposure  
Not classified  
No data available for the product
- i) STOT-repeated exposure  
Not classified  
No data available for the product
- j) aspiration hazard  
Not classified  
No data available for the product

Toxicological information of the main substances found in the product:

ethylene glycol - CAS: 107-21-1

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Mouse > 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2.5 mg/l - Duration: 6h

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

LD50 (RAT) ORAL: 6560 MG/KG

LD50 (RABBIT) SKIN: 4120 MG/KG

---

## SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ECLAT\_WALL PAINTING

The product is classified: Aquatic Chronic 3 - H412

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

ethylene glycol - CAS: 107-21-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 72860 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish 15380 mg/l - Notes: Pimephales promelas

## Safety Data Sheet

### ECLAT\_WALL PAINTING

- Endpoint: NOEC 8590 mg/l - Notes: Ceriodaphnia sp.  
terbutryn - CAS: 886-50-0  
reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and  
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9
- a) Aquatic acute toxicity:
- Endpoint: EC50 - Species: Daphnia 0.1 mg/l - Duration h: 48 - Notes: daphnia magna
  - Endpoint: EC50 - Species: Algae 0.048 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata
  - Endpoint: EC50 - Species: Fish 0.22 mg/l - Duration h: 96 - Notes: oncorhynchus mykiss
  - Endpoint: NOEC - Species: Algae 0.00064 mg/l - Duration h: 48 - Notes: skeletonema costatum
  - Endpoint: NOEC - Species: Daphnia 0.004 mg/l - Duration h: 504 - Notes: daphnia magna
  - Endpoint: NOEC - Species: Fish 0.098 mg/l - Duration h: 672 - Notes: oncorhynchus mykiss
  - Endpoint: NOEC - Species: Algae 0.0012 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata
- 12.2. Persistence and degradability  
N.A.
- 12.3. Bioaccumulative potential  
N.A.
- 12.4. Mobility in soil  
N.A.
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

---

#### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover if possible. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

- 14.1. UN number  
Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name  
N.A.
- 14.3. Transport hazard class(es)  
N.A.
- 14.4. Packing group  
N.A.
- 14.5. Environmental hazards  
N.A.
- 14.6. Special precautions for user  
limited quantity:  
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) 2015/830

## Safety Data Sheet

### ECLAT\_WALL PAINTING

Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 55

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### SECTION 16: Other information

Full text of phrases referred to in Section 3:

H319 Causes serious eye irritation.

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H330 Fatal if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H410 Very toxic to aquatic life with long lasting effects.

H314 Causes severe skin burns and eye damage.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

Hazard class and hazard category	Code	Description
Acute Tox. 1	3.1/1/Inhal	Acute toxicity (inhalation), Category 1
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2



## Safety Data Sheet

### ECLAT\_WALL PAINTING

Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Skin Sens. 1B	3.4.2/1B	Skin Sensitisation, Category 1B
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"

## Safety Data Sheet

### ECLAT\_WALL PAINTING

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.