

CONCRETE

by Novacolor

Intonachino acril-silossanico
fine per esterni, anti-alga,
ad effetto cemento

novacolorTM
I colori dell'Architettura





CONCRETE by Novacolor

Anti-algae acrylic-siloxane plaster coating for exteriors, with concrete feel

INTONACHINO ACRIL-SILOSSANICO FINE PER
ESTERNI, ANTI-ALGA, AD EFFETTO CEMENTO

Applicare in due strati con spatola inox o in plastica.

È possibile decorare ulteriormente la superficie applicando, su supporto completamente asciutto, uno o più strati di Fase Silossanica.

Resa: 1,6-2 Kg/m² in due strati.
Per maggiori informazioni consultare la scheda tecnica.

ANTI-ALGAE ACRYLIC-SILOXANE PLASTER COATING
FOR EXTERIORS, WITH CONCRETE FEEL

Apply two layers with a stainless steel or a plastic trowel. Once the substrate is completely dry, it is possible to enhance the effect with the application of one or two layers of Fase Silossanica.

Yield: 1,6-2 Kg/m² in two layers.
For more information, please check the technical data sheet.

ENDUIT À LA CHAUX ACRYL SILOXANE
ANTI-MOISSURE POUR EXTÉRIEURS

Appliquer deux couches avec truelle inox ou en plastique. Il est possible de décorer ultérieurement la surface, une fois sèche, en appliquant après le séchage complet une ou deux couches de Fase Silossanica.

Rendement: 1,6-2 Kg/m² en deux couches.
Pour plus d'informations consulter la fiche technique.

ALGENFESTER ACRYL-SILOXAN-FEINPUTZ,
FÜR AUßENBEREICHE

Concrete by Novacolor in zwei Schichten mit Kunststoff oder Stahlspachtel auftragen. Die Oberfläche kann mit Fase Silossanica, Lasur-Technik für Innen und Außen-Bereich weiter dekoriert werden.

Ergiebigkeit: 1,6-2 Kg/m² in zwei Schichten.
Für weitere Infos bitte siehe Technisches Merkblatt.



CONCRETE by Novacolor 4654 PC2010 & FASE SILOSSANICA FS 6101 & RUSTON METAL SILVER



CONCRETE by Novacolor 4654 PC 2010 & FS 6101
& FS 6110



CONCRETE by Novacolor 17007 & FS 6112



CONCRETE by Novacolor BIANCO & FS 6101 & RUSTON
METAL SILVER

www.novacolor.it



freedot

02/2017

N000156

novacolorTM
I colori dell'Architettura

NOVACOLOR srl - 47122 Forlì - Italia
Tel +39 0543 401840 - fax +39 0543 414585
Via U. Aldrovandi, 10 - info@novacolor.it



NOVACOLOR is committed to reduce the environmental impact by producing friendly materials.

Made in Italy

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL
= ISO 9001 =**

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =**