

Wall2Floor Athena

Adhesion primer for ceramic coatings.

PRODUCT DESCRIPTION Wall2Floor Athena is a product based on acrylic polymer dispersed in water and special additives that give the product excellent adhesion on particularly smooth surfaces such as tiles, stoneware, mosaic or similar.

APPLICATIONS

Applicable on difficult surfaces:

- floor tiles
- stoneware
- mosaic.

IDENTIFICATION CHARACTERISTICS

Density: 1.40 +/- 0.05 g / ml

Viscosity (packaging): 7800 +/- 500 cps at 25 ° C Drying (at 25 ° C and 65% humidity): at

touch 1 hour;

can be painted over after at least 8 hours and no later than 48 hours.

PERFORMANCE CHARACTERISTICS Wall2Floor Athena creates an anchoring connection substrate that must be covered with Wall2Floor Rasal, thus creating the surface suitable for "Wall2Floor system".

SUPPORT PREPARATION

See technical data sheet of "Wall2Floor system".

APPLICATION

On a dry and clean surface, apply, with a short hair roller, a layer of Wall2Floor Athena.

For more information consult the technical data sheet of the "Wall2Floor system".

DILUTION

The product is ready for use, maximum dilution 10% with water. Shake well before use.

RECOMMENDATIONS

During all phases of preparation of the substrate, products and application, the correct use of equipment and personal protective equipment (dpi) is recommended.

Do not expose the products for long periods to direct heat sources or temperatures below + 5 ° C.

If the products are stored at temperatures close to + 5 ° C, we recommend that you take them to a suitable temperature before use, in order to condition them at a temperature of use not lower than + 10 ° C. Do not heat the products using a direct source of heat, flame, hot body or similar. We recommend that you finish each job with materials from the same manufacturing batch. In the case of use of different manufactures it is advisable to mix the various productions together.

CLEANING OF TOOLS

With water immediately after use.

SURRENDER

Wall2Floor Athena: 15-20 m² l, per single layer, based on the type of substrate.

COLORS

White, not tinted.

PACKING

1 l packs; 5 l; 15 l

STORAGE TERMS

The material has a duration in the original and well sealed container of about 24 months as long as it is stored in a covered warehouse at a temperature between + 10 ° C and + 30 ° C.

SAFETY INDICATIONS

EU limit value (Dir. 2004/42 / EC)

Cat. I: single-component, high-performance paints (water based): 140 g / l (2010)

This product contains max: 140 g / l of VOC

The product does not require labeling in accordance with the regulations in force.

Use the product according to current hygiene and safety standards. Do not throw residues into sewers, waterways and on the ground; after use do not disperse the containers in the environment, allow the residues to dry well and treat them as special waste. Keep out of reach of children. If swallowed, seek medical advice immediately. For further information consult the safety data sheet.

NB- COLORIFICIO NOVACOLOR guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge; however, it cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for each specific case. This cancels and replaces any previous card.