

Wall2Floor Maintenance Wax

Polishing wax to maintain indoor surfaces in Wall2Floor

DESCRIPTION

Wall2Floor Maintenance Wax is a self-polishing liquid wax specifically for maintenance of indoor surfaces of the **Wall2Floor system**.

Wall2Floor Maintenance Wax creates a sacrificial layer that helps protect the surface from dirt and scratches deriving from everyday use.

USES

Applicable on horizontal and vertical indoor surfaces, coated with **Wall2Floor system**.

Wall2Floor Maintenance Wax must be applied as a last layer, over at least two coats of one of the Clear Finish protective finishes (Glossy, Satin, Matt, Countertop, Countertop Ultra Matt).

IDENTIFICATION FEATURES

Binder nature: compound of waxes in water-based emulsion.

Density:

Wall2Floor Maintenance Wax: 1.00 +/- 0.05 g/ml

Drying (at 25 °C and 65% R.U.): to touch in 2 hours; treadable after 4 hours.

DILUTION

Wall2Floor Maintenance Wax: ready to use.

WARNINGS

Mix the material adequately before laying.

Do not apply on damp substrates.

After application, the surface must not come in contact with any type of liquid for at least 24 hours. The first cleaning operations must be carried out after hardening, in general after at least **1-2 days** (calculated at an average temperature of 25°C and with 60% humidity)

Avoid highly abrasive products for cleaning and do not use steam cleaners and brushing machines.

ENVIRONMENTAL CONDITIONS

The surfaces must be protected from frost and drastic changes in temperature during the entire operating cycle. Do not apply with the temperature of the air, substrate and product under +10° C or over +35° C, or in direct sunlight or on a heated surface (even if already in the shade) or on damp or wet surfaces.

The conditions of the environment and the substrate to proceed with application of **Wall2Floor Maintenance Wax** are:

Environmental temperature: Min. +10 °C / Max. +35 °C

Environmental relative humidity: <75%

Substrate temperature: Min. +10 °C / Max. +35 °C

Substrate relative humidity: <4%

Application in different conditions to those described could cause deformity or defects in the chemical-physical properties and aesthetic appearance of **Wall2Floor Maintenance Wax**.

SUBSTRATE PREPARATION

The surface must be clean and dry, consistent and compact, dust-free and free of salt stains caused by humidity.

For further information, consult the technical data sheet for the "**Wall2Floor System**".

APPLICATION

On the dry and clean substrate, with a wax applicator or damp cloth, distribute a layer of **Wall2Floor Maintenance Wax**.

Distribute the product evenly on all the surfaces to treat.

RECOMMENDATIONS

During all the phases to prepare the substrate, the products and application, you are advised to correctly use the equipment and personal protective equipment (PPE).

Do not expose the products for long periods to direct sources of heat or temperatures under +5°C.

If storing products at a temperature around +5°C, you are advised to bring them, before use, to a location with adequate temperature, to condition them at a use temperature not under +10°C. Don't heat the products using a direct source of heat, flame, warm body or similar.

CLEANING EQUIPMENT

With water, immediately after use.

YIELD

Wall2Floor Maintenance Wax: 8-15 m²/l, based on the type of substrate and its absorption rate and application technique used. It is advisable to determine the real yield with a preliminary test on the specific substrate.

COLOURS

Colourless, cannot be tinted.

PACKAGING

1 l packaging.

SHELF LIFE

The product should preferably be used within 1 year of the production date if kept in the original containers unopened and in adequate temperature conditions.

The product does not require labelling pursuant to legislation in force.

Use the product according to hygiene and safety standards in force. Do not throw residue in sewers, in rivers and streams and on the ground; after use, do not dispose of the containers in the environment, leave the residue to dry well and treat as special waste. Keep out of reach of children. If ingested, consult a doctor immediately.

For further information, consult the safety data sheet.

N.B.- COLORIFICIO NOVACOLOR guarantees the information in this data sheet is provided to the best of its experience and technical and scientific knowledge; nonetheless, the company cannot be held liable for the results obtained using these products, as application conditions are beyond its control. You are advised to always ensure the product is suited to each specific case. This data sheet voids and replaces any previously existing data sheet.

Technical data sheet: Wall2Floor Maintenance Wax
Review no.: 01
Date compiled: 14-11-2018
Page 2 of 2